

3M™ No Touch™ Push-to-Fit Earplugs

Technical Data Sheet

Product description

3M™ No-Touch™ corded push-to-fit foam earplugs create a hygienic, noise-reducing seal in the ear canal with soft foam, a smooth tapered shape and paddle stems. Push-to-fit design makes fitting hearing protection easy.

Features

- Easier to insert with fitting paddle; simply push the foam ear plug tips into the ear with the paddle grip
- No need to touch foam ear plug tips to insert helps to keep ear plug tips cleaner longer
- Foam ear plug tips stay clean, even when your hands are dirty
- SLC_{80} 25dB (Class 4)
- Available corded or uncorded


Applications

The 3M™ No Touch™ earplugs are ideal for for a wide range of industrial workplace and leisure environments. Examples of typical applications include:

- Automotive
- Chemical & pharmaceutical manufacture
- Construction
- Heavy engineering
- Metal processing
- Textile manufacture
- Woodworking

Standards

These hearing protectors have been produced to comply with the requirements of the Australian /New Zealand Standard AS/NZS 1270:2002.



Laboratory Attenuation Values

Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean (dB)	25.9	27.3	29.3	30.6	34.9	43.3	45.0
SD (dB)	7.1	7.7	8.7	9.3	7.4	8.6	9.3
Mean - SD (dB)	18.8	19.6	20.6	21.3	27.5	34.7	35.7

SLC_{80} 25dB (Class 4)

3M strongly recommends personal fit testing of hearing protectors. Research suggests that users may receive less noise reduction than indicated by the attenuation label value(s) on the packaging due to variation in fit, fitting skill, and motivation of the user.

Hearing protector Class 4 tested to AS/NZS 1270. When selected, used and maintained as specified in AS/NZS 1269, this protector may be used in noise 100dB(A) to less than 105dB(A), assuming an 85dB(A) criterion.

A lower criterion may require a higher protector class.

Mean = Mean attenuation value derived from testing in accordance with AS/NZS 1270:2002.

SD = Standard Deviation derived from testing in accordance with AS/NZS 1270:2002.

Mean-SD = Mean attenuation value minus Standard Deviation

SLC80 = Single number rating commonly used in Australia and New Zealand to compare acoustic performance of hearing protectors. The subscript '80' indicates that in well managed hearing protector programs, the protection provided is expected to equal or exceed the SLC_{80} in 80% of protector-wearer noise spectrum combinations.

Class = A simplified process for selecting hearing protectors based on the wearers 8-hour equivalent continuous A-weighted sound pressure level.

Materials

The following materials are used in the manufacture of this product.

Component	Material
Earplugs	Polyurethane foam
Cord	PVC

Storage

Store in an area free of contamination.

Do not leave your hearing protection device in areas or locations where it can be exposed to damage or contamination.

Sunlight is particularly damaging as UV light can have a detrimental effect on the materials the product is made from.

Chemical contamination can also have a serious effect on product integrity and decontamination after use is recommended.

Use a suitable storage container especially if left in a vehicle. This will protect the hearing protection device from damage and extend its working life.

Ordering Information

3M Order Code	Model #	Description
70071515624	P2000	3M™ No Touch™ Uncorded
70071515616	P2001	3M™ No Touch™ Corded
70071650231	393-2013-50	3M™ No Touch™ Probed Test Plug

WARNING! Hearing Protection Products

These hearing protectors help reduce exposure to hazardous noise and other loud sounds. Misuse or failure to wear hearing protectors at all times that you are exposed to noise may result in hearing loss or injury. For proper use, see supervisor, User instructions, or call 3M TechAssist Helpline 1800 024 46.

Important Notice: To the extent permitted by law, 3M shall not be liable for any loss or damage including any loss of business, loss of profits, or for any indirect, special, incidental or consequential loss or damage arising from reliance upon any information herein provided by 3M. Nothing in this statement will be deemed to exclude or restrict 3M's liability for death or personal injury arising from its negligence.



3M Australia Pty Ltd
Personal Safety Division
Bldg A, 1 Rivett Road
North Ryde NSW 2113

TechAssist Helpline 1800 024 464
Customer Service 1300 363 565
Email techassist@mmm.com
Web www.3M.com.au/ppesafety

3M New Zealand Ltd
Personal Safety Division
94 Apollo Drive, Rosedale
Auckland 0632

TechAssist Helpline 0800 364 357
Customer Service 0800 252 627
Email 3mnzibt@mmm.com
Web www.3m.com.nz/ppesafety

3M and No Touch are trademarks of 3M.
© 3M 2022. All rights reserved.
AV